



unbalanced

SOMMER CABLE - SC-ONYX 2008**THE TWIN CABLE...**

is similar in construction and quality to the TRICONE MKII, but a little thinner due to the twin-construction. It is suitable for the fabrication of HiFi-cables, adapters and for permanent installation. And it fits almost all jack and RCA connectors. The SC-ONYX can be split at the center of the cable. Each wire has its own copper spiral shielding and is equipped with a thick jacket. The insulation is identified in either white and red, respectively white and yellow (SC-ONYX 2008). The SC-ONYX 2008 is very small in diameter making it ideal for the manufacture of mini-jack plugs.

Also available as a single cable (diode cable) SC-ONYX-TYNEE.

THE ADVANTAGES:

- Very flexible due to the use of fine individual stranding
- Every conductor is insulated and individually shielded with copper spiral shielding
- Manual separation of the cable is easy
- Small jacket diameter, ensuring easy handling with jack RCA and jack connectors

THE APPLICATION:

- Cabling for unbalanced units (keyboards)
- Connection of HiFi-units
- Construction of Y-adapter cables
- Manufacture of insert cables

TECHNICAL DATA:

Construction	LI2YDY2x0,08mm ²
Jacket, outer dimension	PVC 2,6 x 5,9 mm
AWG	28
No. of inner conductors	2 x 1 x 0,08 mm ²
Copper strand per conductor	10 x 0,10 mm
Conductor insulation	PE Lupolen
Shielding	copper spiral shielding
Shielding factor	90 %
Temperature range	min. -20 °C
Temperature range	max. 70 °C
Fire load per m	0,20 kWh
Weight per 1 m	29 g
Packaging	100 m roll
Colour	■ black

ELECTRICAL DATA:

Capac. cond./shield. per 1 m	< 200 pF
Cond. resistance per 1 km	220 Ohm
Insulat. resistance per 1 km	min. 200 MOhm

ORDER DATA: 320-0061